

**S.C.TMK - ARTROM S.A.**

Draganesti Street, No. 30, 230119, SLATINA, OLT, ROMANIA
Tel: +40-249-436862 (top management), 434640, 434641; Fax: +40-249-434330, 437288
E-mail: office.slatina@tmk-artrom.eu; www.tmk-artrom.eu
J 28/9/1991; VAT No: RO 1510210/1992;
Subscribed and Paid Share Capital: 291.587.538, 34 lei

DECLARATION OF PERFORMANCE**No. 3 / CPR 10-06-13**

1. Unique identification code of the product-type: **hot finished structural hollow sections acc. to EN 10210-1**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4): **S275JOH according to EN 10210-1&2:2006**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Metal structures or in composite metal and concrete structures

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

S.C. TMK-ARTROM S.A.,



**Draganesti Street, No. 30, 230119
Slatina, OLT**

Email: office.slatina@tmk-artrom.eu

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**S.C. TMK-ARTROM S.A.,
Draganesti Street, No. 30, 230119
Slatina, OLT**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **2+**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: **EN 10210-1&2**

Notified factory production control certification body No. 0036 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.

0036- CPR-M-08-2011

Cod: FCU-01, Ed.2 Rev. 8/2012

8. Declared performance

S275J0H, EN 10210-1:2006

Essential characteristic	Performance				
Tolerances on dimensions and shape	Outside dimensions		±1% with a minimum of ±0.5mm and a maximum of ±10 mm		
	Thickness		±10%		
Yield strenght	Nominal thickness (mm)		Values		
	>	≤	min. (MPa)		
		16	275		
	16	40	265		
	40	63	255		
Tensile strength	Nominal thickness (mm)		Values		
	>	≤	min. (%)	max. (%)	
		3	430	580	
	3	100	410	560	
Elongation	Nominal thickness (mm)		Values		
	>	≤	min. (%)		
		40	23		
	40	63	22		
Impact strength	Nominal thickness (mm)		Values		
	≥		min. (J)		
	6		27J at 0°C		
Durability			Elem.	min. (%)	max. (%)
			C	0.20	0.22
			Mn		1.50
			P		0.035
			S		0.035
			N		0.009

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: **EN 10210-1&2:2006**

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Silviu Barbulescu – Chief of Quality Control & Laboratories
Slatina June 10, 2013





0036- CPR-M-08-2011

TMK-ARTROM S.A.
Draganesti Street, No.30, 230119, SLATINA, OLT, ROMANIA

13

No. 3 / CPR 10-06-13

EN 10210-1:2006

S275JOH / 1.0149

intended to be used in metal structures or in composite metal and concrete structures

Tolerances:**Elongation:****Tensile strength:****Yield strength:****Impact strength:****Weldability:****Durability:**

expressed as indicated in the
DoP

Dangerous substance: No performance determined