

Declaration of Performance (DoP): Nr.Gnk.11.02

Stainless steel for construction purposes EU-regulation: 305/2011

Genk site / 1.4571 / Cold-rolled-work-hardened (Temper)

1.

Product-type: 1.4571

2

Construction product: Cold-rolled-work hardened (temper) stainless steel coils, plates, sheets according to EN

10088-4

3.

Intended use: products for internal and external use for construction purposes, building constructions or civil

engineering

4.

Manufacturer:

APERAM GENK SWINNENWIJERWEG 5 3600 GENK BELGIUM

Tel: +32 (0)89 30 21 11

E-mail: Stefaan.Maes@aperam.com

Website: http://www.aperam.com/http://www.aperam.com/europe/news-

publications/documentation/certifications/approvals

5.

Authorised representative :Not applicable

6.

System of assessment and verification of constancy of performance: System 2+

7.

Case of the declaration of performance concerning a construction product by a harmonized standard:

TûV SûD Industrie Service GmbH, Nr. 0036, has performed the initial inspection of the factory and factory production control and monitoring, review and approval of the factory production control according to system 2+ and issued a conformity certificate of production control:

Aperam Genk : "0036 - CPR - M - 43 - 2011"

8

Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :

Not applicable

DoP.NR.GNK.11.02 REV.0 (page 1 of 3)

9. Declared performance :

Performance for 1.4571			Harmonised technical specification	
Finish				
temper 2H		EN ISO 9445-2		
tomnor.		min(Mpa)	max(Mpa)	
2H	CP350	350	500	EN 10088-4
temper 2H	CP500	500	700	
temper 2H	C700	700	850	
temper 2H	C850	850	1000	
temper 2H		chemical composition		
temper 2H		chemical composition		
		Values		
temper 2H		C ≤ 0,080		EN 10088-4
		Si ≤1.00		
		Mn ≤ 2.00		
		P < 0,045		
		· · · · · · · · · · · · · · · · · · ·		
		1110. 2.0 - 2,0		
	emper 2H emper 2H emper 2H emper 2H emper 2H	emper 2H CP350 emper 2H C700 emper 2H C850 emper 2H em	Emper 2H EN ISO 9445-2 Values min(Mpa) emper 2H CP350 350 emper 2H CP500 500 emper 2H C850 850 emper 2H chemical composition emper 2H chemical composition emper 2H C ≤ 0,080 emper 2H C ≤ 0,080 Si ≤1.00 Mn ≤ 2.00	Emper 2H EN ISO 9445-2

10.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by Joost Vantrappen - Head Customer Service Genk, 07/02/2014

A