



Declaration of quality properties
According European building materials directive Nr. 305/2011,
Annex III

Nr. S235JRH-CPR-2013/07

1. An unique registered identification number of the product:

S235JRH according EN10219-1

2. Identification of the construction product:

See marks on the label

3. Intended use of the product:

Welded hollow steel profile from unalloyed and fine grain steel for building from steel constructions

4. Manufacturer:

PAO "Kominmet"

Komintern str., 7

Dnepropetrovsk

49023 Ukraine

Phone/fax (056) 721 01 51

email: kominmet@yandex.ru, www.kominmet.com.ua

5. The authorized representative of the manufacturer, acting on authority according section 2 article 12:

Not applicable

6. Assessment system for stability of performance characteristics:

System 2+

7. Name and ID of a notified body, which granted allowance:

The registered body for certification of construction products and steel constructions Nr. 0090 TÜV Thüringen e.V. (Erfurt, Germany) has performed a primary test of the plant and the plant production control system and makes process control, assessment and acknowledgement of the plant production control according with ZAEN 10219-1:2006. The certificate is issued.

8. Declaration for construction products, for which the European technical certification was given:

Not applicable



№ S235JRH-CPR-2013/07

Page 1 of 2

9. Declared technical data:

Essential characteristics	Operational characteristics		Harmonised technical requirements						
Minimum yield strength of metal	Thickness of wall, mm	R_{eH} , МПа	EN 10219:2006						
	≤16 >16≤40	235 235							
Tensile strength	Thickness of wall, mm	R_m , МПа	EN 10219:2006						
	≤3 >3≤40	360-510 360-510							
Minimum extension at destruction	Thickness of wall, mm	A, %	EN 10219:2006						
	≤40	24							
Minimum impact work	Test temperature, °C	KV ^o , J	EN 10219:2006						
	+20	27							
Chemical composition	Maximum weight content, %							EN 10219:2006	
	C	Si	Mn	P	S	S	N		
	0,17	-	1,40	0,04	0,04	0,04	0,009	0,35	

10. Confirmation:

The performance characteristics of products, indicated in items 1 and 2 correspond to declared in item 9 performance characteristics. This declaration of performance characteristics is issued for responsibility of the manufacturer indicated in item 4.

Signed from Manufacturer:


Technical Director – Authorized for quality

Name and position

A.S. Roslik

Dnepropetrovsk 2013/07/01

Place and date of issue



In original signed

№ S235JRH-CPR-2013/07

Page 2 of 2

Результаты испытаний

Test result

Химический состав стали				Chemical steel composition			
№ плавки Heat №	Массовая доля элементов, %			Element mass fraction, %			
	C x 100	Mn x 100	Si x 100	S x 1000	P x 1000	Al	N
36261/1	12	42	8	37	10		
131840	7	44	1	35	10		

Номер партии Lot №	№ плавки Heat №	Механические свойства Mechanical properties					Технологические свойства Technical properties					
		Темпер. испыт. Test temperat t. °C	Предел. текучес. Yield strength КГ/ММ2	Предел. прочн. Tensile strength КГ/ММ2	Удлинение Elongation		Работа удара Activity of Impact KV(-20) 150/ Dg	Сплюс- чивание Flatte- ning test	Раздача Drift test	Загиб Bend- over test	Не разруш. контроль Nondest- ructive inspec- tion %	Гидро- испы- тание Hydro- testing %
					A	A						
					L=80 %	L=5,65 √ So, %						
1	36261/1		45.40	51.90		24.00					100	
2	131840		38.80	42.20		42.50					100	

- Примечание:** 1. Визуальный контроль, маркировка и упаковка без замечаний.
Note: Visual inspection marking and packing - without remarks.
 2. Размеры труб в пределах допусков.
 Pipe dimensions are permitted:
 3. Процесс выплавки (melting process) - Y
 4. Декларация характеристик качества № S235JRH-CPR-2013/07,
 см. на сайте www.kominmet.com.ua
 Declaration of quality properties Nr. S235JRH-CPR-2013/07,
 see in the Site www.kominmet.com.ua

Указанные в настоящем документе трубы соответствуют по качеству условиям контракта.
 Those in this paper tube is equal to the quality terms of the contract.

 12 0090	Подпись эксперта Signature expert _____ Штамп эксперта Stamp expert
---	--